Collamat C-Series Label Applicators

Swiss modular labellers

Collamat C-Series label applicators all share the same compact, modular design allowing a choice of dispense speed, label roll size and application module to suit the application requirements.

Applicator modules include roll-on, tamp, blow and corner-wrap. For applications where a standard module is not suitable, customised application modules can be designed and installed.

The modular design makes it easy to install a choice of print modules for print-and-apply applications.

Whether you need a simple 15m/min applicator or a high-speed 50m/min fully inline system, all Collamat systems share the same industrial build quality and modular design.

Simple controls allow system settings such as label position and dispensing speed to be quickly adjusted.

automatic inline systems

As well as supplying applicators to work on existing product conveyors, Martek also produces fully automatic inline systems to suit individual requirements.

Automatic systems include:

- Single and two-side labellers
- Wrap-around labellers for bottles, jars, cans etc.
- Top, bottom and top-and-bottom labellers
- Magazine-fed tube labellers
- Carton and sleeve feeder-labellers

All systems can be constructed from stainless steel for clean environments.

print-and-apply options

Due to their modular design, all Collamat applicators can be fitted with a choice of print modules for print-and-apply applications.

This can be as simple as a low-cost thermal transfer coder for adding batch codes to pre-printed labels or a thermal transfer print engine for printing the entire label.

By separating printing and label application processes, printing is kept slow for optimum print quality whilst labels are applied at high speed.

Specification

	2610	4310	7310	4320	7320
Max. label width:	95mm	95mm	95mm	160mm	160mm
Max. speed:	15m/min	25m/min	50m/min	25m/min	50m/min
Accuracy:	+/- 1mm	+/- 0.7mm	+/- 0.7mm	+/- 0.7mm	+/- 0.7mm
Label roll size:	250mm	250 or 350mm	250or 350mm	250 or 350mm	250 or 350mm
Label core:	40 to 76mm	40 to 76mm	40 to 76mm	40 to 76mm	40 to 76mm
Min. label length:	10mm	10mm	10mm	10mm	10mm
Power supply:	110/240Vac	110/240Vac	110/240Vac	110/240Vac	110/240Vac