



## Technical Data

# AEROSOL-CANS

Aluminium, monobloc  
in accordance  
with EN 15 008

## Material

- Aluminium 99,5

## Manufacturing process

- Impact extruded without seam, shoulders being formed afterwards

## Dimensions and finish

- Round, flat, and special shoulder
- Test pressure 12, 15 and 18 bar
- Opening corresponds to EN 15 006
- Shapes customized
- Embossing

## Internal coating

- Internal lacquer applied in two layers and adapted to filling product
- Powder coating, solvent free
- Partial lacquering

## Decoration

- Brushed finish
- Outside lacquer: clear, white or coloured
- Special-effect-lacquer: flitter and pearlescent
- Dry-Offset printing up to 8 colours
- Additional decoration can be achieved by half tone and irisated print
- Clear outside varnish, brilliant, mat and special-effect-lacquers



[www.tubex.de](http://www.tubex.de)



Technical Data

## AEROSOL CANS

TUBEX-Standard sizes  
1" Opening EN 15 006

Brimfull capacity (ml)	Fill volume (ml)		Dimension (mm)	
	Liquid gas	Compressed gas	diameter	height
54	30	-	35	65
59	35	-	35	70
75	50	-	35	88
89	-	50	35	105
110	75	-	35	127
140	100	75	35	156
			45	105
175	125	100	45	128
210	150	125	45	150
			50	125
			53	110
270	200	150	45	190
			50	156
			53	142
335	250	200	50	190
			53	173
405	300	250	50	225
			53	205
480	375	-	59	201