

**CombiPac 130 x 94**

**Product no:** Still-07-L040  
**Shape:** Rectangular



**DIMENSIONS**

External length top:	129.6 mm ± 1 mm	External width top:	94.3 mm ± 1 mm
Height:	9 mm ± 0.5 mm		

**WEIGHT**

Weight Plastic:	4.8 g	Weight Paperboard Insert:	1.7 g
-----------------	-------	---------------------------	-------

**PERFORMANCE**

**Compression tests**      The compression test refers to a static load and has been performed with the standard raw material as stated above. With respect to the dynamic load during transportation, it is advisable that the customer makes internal transport trials for filled products when applicable.

**DECORATION**

Decoration available:      Paperboard Insert

**RAW MATERIAL (MECHANICAL PROPERTIES)**

Raw material options:      rPET

Masterbatch colours:      Colours according to Berry standard selected pantone colours.

**Hot temperatures:**      For products requiring hot filling, thermoformed PP-packaging are preferred to PS- or APET-packaging. The Berry packaging must be tested by the customer with the actual product before approval for use at hot temperatures. For CombiPac and CombiRound, please ask your sales contact, as alternative materials can be discussed for hot filling tests.

**Cold temperatures:**      Freezing conditions require special resins available on request. The Berry packaging must be tested by the customer with the actual product before approval for use at low temperatures.

**QUALITY SPECIFICATIONS**

**Approvals:**      This Berry Product complies with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

**Shelf life:**      The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.

**Quality information:**      Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.

**Compliance and product suitability:** For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.