




D9100SW

FR Waterseal Tape & Corrosion Inhibitor



- Backing:** Interior-Grade Aromatic Polyurethane
- Adhesive:** Urethane-based
- Liner:** N/A
- Colors:** Transparent
- Specifications:** FAR 25.853(a), BMS 8-346 Type I & II Class 1, Airbus 10-05-004, ABS 5093, and ABD 0031 Para 7.3.2 and 7.4; Fokker Fk05-193
NSN 8030-01-542-1415
- Size Options:** Incremental sizes 1/4" - 48" x 108Ft

Applications

- Floor joint sealing on aircraft decking in all wet areas including: entryways, galleys, lavatories, and more
- Moisture barrier applications
- Surface protection for high wear areas
- Sound damping

Features

- Polyurethane Film Backing
- Urethane-Based Adhesive
- Self wound

Benefits

- Protects and holds under heavy usage
- Tough and durable - abrasion resistant
- Conformable for curves and irregular surfaces
- Transparent to allow for visual inspection
- Strong permanent bond
- Can be applied directly over wet sealant
- Easy to use
- No release liner to discard - less waste

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	9.0 mils	0.229 mm	PSTC-133
Substrate Thickness	7.0 mils	0.178 mm	PSTC-133
Adhesion to Steel	75 oz/in	8.21 N/cm	ASTM D-3330
Tensile Strength	70 lb/in	122.59 N/cm	ASTM D-3759
Puncture Resistance	25 lbs	11.34 kg	ASTM D-1000
Elongation	600%		
Weight	8.64 oz/yd ²	292.95 g/m ²	
Abrasion/Wear Index	0.98		ASTM D-4060
Application Temperature	50°F to 120°F	10°C to 49°C	
Operating Temperature	-65°F to 300°F	-54°C to 148°C	

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F
Standard Shelf Life (at 25 °C): 24 months from date of manufacture

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY GLOBAL assumes any legal responsibility.

