
444B

HVAC Line Set Tape



Backing: OPP Film

Adhesive: Acrylic

Liner: N/A

Colors: Black - Printed or Unprinted

Specifications: N/A

Standard Sizes: 48mm x 55M

Applications

 Wrapping and protecting foam insulation for pipes and line sets

Features Benefits

OPP Backing	 Tough and durable
	 Hand tearable for ease of use
	 UV Resistant for outdoor installations*
 Acrylic Adhesive 	 Solvent-Free for reduced odor
	 Aggressive bond - won't flag or lift
	 Mold and moisture resistant
 Low VOC Content 	 Can contribute toward satisfying EQ Credit (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.0 mils	0.076 mm	ASTM D-1000
Adhesion to Steel	45 oz/in	4.92 N/cm	PSTC-101
Adhesion to Backing	35 oz/in	3.83 N/cm	PSTC-101
Tensile Strength	32 lb/in	56.04 N/cm	ASTM D-1000
Operating Temperature	-40 to 212 °F	-40 to 100 °C	
VOC Content	<1 g/L		

^{*}Not recommended for rooftop applications

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use compiles with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation forwhich Berry Global assumes any legal responsibility.

