



Nashua[®]
TAPE PRODUCTS

NEW UVSIX[™]

NEW NASHUA HIGH-PERFORMANCE DUCT TAPE

SIX-MONTH UV RESISTANCE, WATER RESISTANCE AND ON-THE-JOB PERFORMANCE

Introducing the next generation of high-performance duct tape. With 6-month UV resistance, residue-free removal, superior water resistance, and an easy tear-by-hand design, it's built to handle the toughest conditions. Engineered to cover your six.



**1 SUPERIOR 6-MONTH
UV RESISTANCE WITH
RESIDUE-FREE REMOVAL**

ENGINEERED FOR THE OUTDOORS

UV-resistant tape that stands up to sun, wind, and rain. Holds strong and removes cleanly every time—no residue, even after six months of exposure.



**2 WATER-RESISTANT
APPLICATION**

INSTANT GRIP, LASTING SEAL

Bonds instantly to almost any surface. Throw UVSix into a challenging situation, delivering a tight, moisture-resistant seal every single time.




**3 MORE EFFECTIVE
THAN EVER BEFORE**

FINISH THE JOB FASTER

UVSix's tough cloth reinforcement tears easily, while its adhesive instantly grips any surface—rough or smooth. The bottom line: fast, reliable, and so effective you'll set it and forget it.

UVSIX™ CLEAN REMOVAL DUCT TAPE

	BACKING	PE Coated Cloth
	ADHESIVE	Rubber
	LINER	N/A
	COLORS	Slate Blue and Red
	STANDARD SIZES	48mm x 55m 72mm x 55m
APPLICATIONS	<ul style="list-style-type: none"> • Multiple uses in powerplants and on ships • Media-blast protection • Heavy-duty packaging and bundling • Holding dosimeters, securing clothing and gloves, wrapping pipe ends, insulation and duct sealing • Color coding 	
FEATURES AND BENEFITS	PE-COATED CLOTH BACKING	<ul style="list-style-type: none"> • High tensile strength for difficult applications • Abrasion and puncture resistant • Crisp, straight tear • UV resistant for 6 months
	NATURAL RUBBER-BASED ADHESIVE	<ul style="list-style-type: none"> • Aggressive adhesion - including adhesion to extremely rough materials • Clean removal from most surfaces with little or no residue for up to 6 months

TYPICAL TEST VALUES

	STANDARD UOM	METRIC UOM	TEST METHOD
TOTAL THICKNESS	11.5 mils	0.290 mm	ASTM D-1000
ADHESION TO STEEL	80 oz/in	8.85 N/cm	PSTC-101
TENSILE STRENGTH	26 lb/in	46.00 N/cm	ASTM D-1000
OPERATING TEMPERATURE	40° to 200° F	4° to 93° C	-
ADHESION TO BACKING	45 oz/in	5.00 N/cm	PSTC-101
FLAME SPREAD INDEX	15	-	ASTM E84
SMOKE DEVELOPED INDEX	30	-	ASTM E84

Recommended Storage Conditions: 60°-80° F at 40%-60% RH
Standard Shelf Life (at 25° C): 36 months from date of manufacture.

Nashua®
TAPE PRODUCTS

UVSIX™

**HIGH-PERFORMANCE
6-MONTH
UV-RESISTANT
DUCT TAPE**