

PACKAGING MATERIAL DATA SHEET

General Data

Supplier and Manufacturer: SARONG S.p.a.

Reference Name: ALU/PE

Colours: Metallic grey

Application fields: Forming in Pharmaceutical, Cosmetic and Industrial applications

Products and Specifications

**Materials composed by Tempered Aluminium foil
laminated with PE (Low density Polyethylene)**

Thickness (µm)	Composition	Basis Weight (gr/m ²)	Lamination process	PE type
70	ALU 45µm + PE 25µm (not peelable)	144	Lamination by glue	Not peelable
85	ALU 45µm + PE 40µm (peelable)	158	Lamination by glue	Peelable
73	ALU 47µm + PE 26µm (not peelable)	153	Extrusion coating (compatible with phenolic products)	Not peelable

* Approximate data calculated from unofficial sources

Reel features

Inner core Ø: 70/76 mm • Ext. reel Ø: 300÷500 mm • Reel width: from 50 to 1100 mm

Printing

Printing by Rotogravure in one or two colours

Automatic packaging machines

Main uses: suppository forming/filling/hot sealing machines, the PE layer can peelable (peel-off opening of the packaging) or not peelable (opening by breaking in pre-cut area).



SARONG SpA – 42046 Reggiolo (RE) – Italy – Via C. Colombo, 18
Tel. +39 0522 212511 - Fax +39 0522
www.sarong.it - e-mail: info@sarong.it

