CARDBOARD TUBE





Specifications	
Inside Diameter	From 18 to 204 mm Standard products : 40/50/76/152 mm
Thickness	1 up to 20 mm
Thickness	From 10 mm to 5 meters 7 meters on request
Cut lengths	From 10 mm
Cutting Tolerances	5/10 mm end of spiral winding machine 2/10 mm by recutting after drying
Resistance	According to the standard ISO 11093-9 and regarding specific requirements
Mechanical stability	By steaming for a reduction of the humidity rate until 6%
Raw material	High-strenght cardboard
Tracability	Internal or Outside marking (date and hour)
Printing	Logo by typography or Flexo printing of external coverage cord from: • 1 000 m² for a single colour in planographic printing • 10 000 m² for a customized text
Closure system	Standard plastic stopper / Flange cover or insert cardboard cap
Packaging	Automatic palletizing for the lengthes from 300 mm to 5 meters encircled and filmed according to specifications

Cardboard Core and Ring	For the rolling-up of: Plastic film and plastic sheeting / Labels / Papers and Cardboards / Covers, carpets / Foam and air blister film
Tube for shipping	For Posters and maps / Mailing / Calendar
Tube for protection	For Blinds / Roller blinds / Profiles and metal tubes
Specific tube	Telescopic tubes / Masts for advertisement / Candles

Avantages and Benefits

Constant quality guarantee	A unique successful manufacturing tool which guarantee the gluing and the perfect cutting with on-line dimensional controls and resistance
Mechanichal resistance	Guaranteed by a steaming adapted to every product which can go up 72 hours
Important stock	Storage capacity of 2 500 m ²
French manufacturing	French raw material and factory 100% French ownership.
Single point of contact	Unique person dedicated to the follow-up of order, sampling and product delivery

