

EXCELLENCE IN STRAPPING SOLUTIONS



MO-M-8
Semiautomatic Strapping Machine

EXCELLENCE IN STRAPPING SOLUTIONS

MO-M-8

STANDARD FEATURES

- Thermostatically controlled heat-weld-sealing
- Wear-free DC drive, brushless motor technology
- Easy strap coil change and threading system
- Soft strapping with open sliding position for sensitive packages
- Adjustable strap tension via potentiometer
- Energy-saving drives
- Electronic controls
- Hinged table top made of stainless steel
- 4 castors of which 2 are lockable
- Structural coating RAL 5010, gentian blue
- Strap feed from sealing head level adjustable from 600 – 1.400 mm via potentiometer
- Quiet sealing unit
- Package width min. 80 mm
- Stand-by-operation

OPTION:

Package stop (stop for bank notes)

TECHNICAL DATA

STRAPPING CAPACITY: Depending on the operator

TABLE SIZE: 980 mm x 540 mm

TABLE HEIGHT:820 mm to 900 mm

STRAPS: Standard machine grade

5, 8 or 12 mm wide

PP straps

STRAP COIL DISPENSER:

Core diameter: 200 mm Core width: 190 mm


ELECTRICITY:


Voltage: 100-230 V, 50/60 Hz, 1 PH


Power consumption: approx. 0.12 kW

SEALING UNIT: Standard 3 sealing unit

WEIGHT: 120 kg







10 / 15 Subject to Alterations







EXCELLENCE IN STRAPPING SOLUTIONS

MOSCA GMBH

Gerd-Mosca-Straße 1 D-69429 Waldbrunn/Germany Tel.: +49 6274/932-0

Fax: +49 6274/932-400 118 Tel. Tech. Service: +49 6274/932-146

E-Mail: info@mosca.com Internet: www.mosca.com The models of MO-M-8 are adjustable to one strap width of all quality PP straps of 5, 8 or 12 mm.
Obtainable directly from Mosca, produced in one of Europe's most modern manufacturing plants. Combinable with maintenance contracts by Mosca – a one-stop solution.

