

# DC-338-1 系列液体、粘体高速包装机 Liquid & Viscous High-speed Packaging Machine



## DC-338-1 液体、粘体高速包装机 Liquid & Viscous High-speed Packaging Machine

### DC-338-1 系列包装机械的特点(Characteristics)

DC-338系列机械是针对液体、粘体等物料实现自动包装而设计的三对辊筒的包装机械。该机可以实现三边封口或四边封口的包装。该机采用了先进的工业计算机控制系统。通过“人机对话”，可方便准确地实现制袋尺寸大幅度增长或减短包装速度地调整变化，液晶触摸屏可完成绝大部分功能地设置，中文提示使各项设置操作简单而明确。

该机有一组纵封热辊筒、一组横封热辊筒、一组横封冷辊筒。封口采用辊筒方式，纵向封口花纹采用棋盘纹配合防漏线，被包装地物料通过计量装置落入包装袋中。计量装置可有多种方式选择。如用于液体包装的磁力泵、用于粘体包装的活塞泵及海潮泵。用于粘体包装且必须连续填充的罗塔里泵。切断刀可以采用平刀、锯齿刀、点划线刀三种方式之一。该机还装备有方便开袋的易撕切口装置。整机的电器控制均选用优质的电器元件，其中封口辊筒温度控制采用进口的智能温度控制仪，机器速度控制采用进口的变频器进行调节。该机不需要更换任何零件，可以实现包装长度的无级变化，适合单机多品种的生产。

DC-338-1 is for viscous automatic filling and packaging which adopts a 3-steps roller system. It can achieve 3 or 4 sides sealing. It also adopts advanced industrial computer control system which can adjust the size of the sachets as well as the speed by the inter-communication of the users and machine. Thus it makes your production easier and more accurate. Most of the settings can be performed in the LCD touch screen with English instructions which makes the machine user-friendly and the whole production process simpler.

This machine seals the films with rollers. There are 3 rollers in the machine. One is for vertical heat-sealed, one for horizontal heating, and the other for cool sealing. The vertical and horizontal sealing area adopts the chess dotted line. And the horizontal can also be sealed with straight seal with leakage proof line. This machine has 3 different options for the trimming blades-- straight, sawtooth and dashline. It also equips with notch cut device for the sachets. The products are put into the sachet via piston pump.

### 适合物料(Applicable products)

酱油、止咳露、农药乳油、悬浮液等液体物料、洗发水、护发素、沐浴露、膏霜等。

Mayonnaise, pectoral syrup, meat sauce, curry, shampoo, pesticide, ketchup, cream and salad sauce, etc.

### 技术参数(Specifications)

袋长范围(Pouch Length): 40-120mm或(or)70-160mm

袋宽范围(Pouch Width): 40-85mm

包装速度(Packing Speed): 30-120包/分钟(pic/min)

填充容量(Filling Capacity): 1-12ml 或(or) 10-50ml

(可选)(OPTIONAL)

适应包材(Applicable Film): PET/AL/PE, PET/VMPET/PE, PET/PE, NY/PE, NY/VMPET/PE, etc.

机械功率(Consumption Power): 3.5KW/ AC380V

机械尺寸(Machine Dimensions): 长(L)140cm 宽(W)100cm 高(H)180cm

机械重量(Machine Weight): 约550Kg

超出以上范围的特殊要求可以向大川机械特殊订制。  
Tailor made if the requests beyond the above conditions.

- ◆ 优质不锈钢外壳
- ◆ High Quality Stainless Steel Cover
- ◆ 三段式辊筒封口
- ◆ Sealed With Three Steps Rollers
- ◆ 变频速度控制
- ◆ Inverter Control
- ◆ 智能封口温度控制
- ◆ Intelligent Temperature Check
- ◆ 包装长度任意可调
- ◆ Sachets' length changes as wish

汕头市大川机械有限公司  
SHANTOU DACHUAN MACHINES CO., LTD.

地址: 广东省汕头市华山北路浮西工业区(水厂后)

ADD: Fuxi Industrial Area, Huashan North Road, Shantou

电话/Tel: +86-754-88109233 88107933

传真/Fax: +86-754-88216255

手机/Mob: +86-13076300016 +86-13802715381

网址/Web: <http://www.gd-dachuan.com>

E-mail: [liwen@gd-dachuan.com](mailto:liwen@gd-dachuan.com)

