| Berry Superfos | | | Technical Datasheet |
|--|---|--|---|
| SuperCube Rectangu Product no: 825 Shape: Rectangu | | 65 x 190 mm | |
| DIMENSIONS | | | |
| External length top: | 260.7 mm ± 1 mm | External width top: | 186.5 mm ± 1 mm |
| Height: | 11.1 mm ± 0.5 mm | | |
| WEIGHT | | | |
| Weight: | 57 g ± 3 g | | |
| PERFORMANCE | | | |
| Stacking tests | period of 2 months. Stack | ability depends on many factors and | raw material as stated below at 23°C over a the above data is meant as an indication only. nine the viability of stacking and transportation. |
| CLOSURE SYSTEM | | | |
| Closure type: | Peel-off | | |
| DECORATION | | | |
| Decoration available: | IML | | |
| RAW MATERIAL (MECHANICAL PROPERTIES) | | | |
| Raw material options: | PP | | |
| Masterbatch colours: | Colours according to Berr | y Superfos standard selected panton | e colours. |
| Hot temperatures: | The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures. | | |
| Cold temperatures: | | re special resins available on request actual product before approval for us | . The Berry Superfos packaging must be tested e at low temperatures. |
| QUALITY SPECIFICATIONS | | | |
| Approvals: | amendments, relating to r | naterials and articles intended to con n EU legislation, it is the responsibility | Commission Regulation No. 10/2011/EC with the into contact with food, unless otherwise of the customer to ensure that the supplied |
| Shelf life: | The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period. | | |
| Quality information: | Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery. | | |
| Compliance and product suitabilit | ty: For all information related Compliance. | to food contact compliance and proc | luct suitability ask for the Declaration of |
| www.superfos.com | Specifications ar | e subject to change without notice. | Latest revision: 14-02-2017 |