## **Technical Datasheet**

Product no:8623Shape:RoundAvailable lids:88838873/887488758620 (Membrane)		888 860	8871/8872 8882 8601 (Membrane)		
VOLUME					
Volume brimful:		310 ml			
DIMENSIONS					
External diameter top:		95 mm ± 0.5 mm	95 mm ± 0.5 mm Height: 68.5 mm ± 0.5 mm		0.5 mm
External diameter bottom:		69.6 mm ± 0.5 mm			
WEIGHT					
Weight:		7.7 g ± 0.8 g			
PERFORMANCE					
Stacking tests Special:		period of 2 months. Stac Consequently, customers	been performed to the standa kability depends on many fac s should make internal trials to vave applications,specific test	tors and the above data is a order the order of the order	meant as an indication only. stacking and transportation.
opoolali		use.			
CLOSURE SYSTEM	И				
Lid type options:		Membrane			
Closure type:		Peel-off			
Tamper Evidence ty	pe:	Membrane sealing			
DECORATION					
Decoration available	e:	IML			
RAW MATERIAL (M	IECHANICAL	PROPERTIES)			
Raw material options:		PP			
Hot filling:		For hot filling and microwave applications, specific tests with the actual product must be carried out prior to use.			
Masterbatch colours:		Colours according to Berry Superfos standard selected pantone colours.			
Cold temperatures:		Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.			
QUALITY SPECIFIC	CATIONS				
ar st		All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.			
afte		The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.			
Quality information:		Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.			
Compliance and pro	oduct suitabilit	y: For all information related Compliance.	d to food contact compliance	and product suitability ask	for the Declaration of
www.superfos.com	1	Specifications a	re subject to change without	notice	Latest revision: 31-01-2023