Technical Datasheet

	SuperFlex Ø2 Product no: Shape: Available lids:	282 Round 2267 (Stan 269 (Memb	dard)				
	VOLUME						
	Volume under lid: 8		8.7 l ± 80 ml	Volume brimful:		9.4 ± 8	30 ml
	DIMENSIONS						
	External diameter top: 2		266 mm ± 1 mm	Height:		199.3 n	nm ± 1 mm
	External diameter bottom: 2		241.3 mm ± 1 mm				
	WEIGHT						
	Weight:	2	243 g ± 12 g	Weight	metal handle:	36 g ± 4	4 g
	Weight plastic handle:		24.5 g ± 2 g				
	PERFORMANCE						
	Stackability - dynami	ic:	Max: 56 kg top load on bottom container at 23°				
	Stacking tests		The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.				
	CLOSURE SYSTEM	1			HANDLE		
	Lid type options:		Tamper Evidence, Standard, Membrane		Standard handle: Optional handle:		Metal with roller grip Flexible plastic hanging
	Closure type:		Flex-off				
	Tamper Evidence type:		Tamper Evidence lid				
	DECORATION						
	Decoration available:		Dry Offset				
	Decoration area offset:		770 X 150 mm				
RAW MATERIAL (MECHANICAL PROPERTIES)							
	Raw material options:		PP				
	Hot filling:		Up to 95° C				
	Masterbatch colours:		Colours according to Berry Superfos standard selected pantone colours.				
			The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.				
			Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.				
QUALITY SPECIFICATIONS							
Approvals: All Berry Superfos Products comply with the European Union Commission Re amendments, relating to materials and articles intended to come into contact stated. In accordance with EU legislation, it is the responsibility of the custom product is suitable for the intended use.					with food, unless otherwise		
Shelf life:			The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.				
·			Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.				
Compliance and product suitability:		duct suitability:	For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.				
	www.superfos.com		Specifications are subject to change without notice.				Latest revision: 20-07-2022