Technical Datasheet

Shape: R Available lids: 1	5 mm 32,2 ltr 786 ound 982 (Standard) 996 (Special)			
VOLUME				
Volume under lid:	32.2 l ± 159 ml	Volume brimful:	33.3 l ± 166 ml	
DIMENSIONS				
External diameter top:	374 mm ± 3.7 mm	Height:	418.4 mm ± 4.2 mm	
External diameter botto	om: 304 mm ± 3 mm	U U		
WEIGHT				
Weight:	996 g ± 30 g			
PERFORMANCE				
Stackability - dynamic:	Max: 70 kg top load on bot	tom container at 23°		
Stacking tests The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.				
Special: For the 1996 lid "Stackability filled" is 76 kg.				
CLOSURE SYSTEM		HANDLE		
Lid type options:	Special, Standard	Standard hand	le: Body Grip	
Closure type:	Flex-off, Peel-off			
Tamper Evidence type:	None			
DECORATION				
Decoration available:	Dry Offset			
Decoration area offset:				
RAW MATERIAL (ME	CHANICAL PROPERTIES)			
Raw material options:	PP			
Masterbatch colours:		Colours according to Berry Superfos standard selected pantone colours.		
Hot temperatures: The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.				
Cold temperatures: Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.				
QUALITY SPECIFICA	TIONS			
Approvals:	amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.			
Shelf life:	after the date of the deliver	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.		
Quality information: Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.				
Compliance and produ	ct suitability: For all information related t Compliance.	to food contact compliance and	product suitability ask for the Declaration of	
www.superfos.com	Specifications are	subject to change without notic	e. Latest revision: 13-12-2021	