Technical Datasheet

Shape: R Available lids: 22 22	2 mm 4,8 ltr 245 ound 222 (Standard) 225 (Membrane) 25 (Tamper Evidence)			
	(
VOLUME	4.0 L _ 50 ml			
Volume under lid:	4.8 l ± 50 ml	Volume brimful:	5.1 l ± 50 ml	
DIMENSIONS	000	11-1-1-1	100 5 mm 1 mm	
External diameter top: External diameter botto	222 mm ± 1 mm m: 195.6 mm ± 1 mm	Height:	162.5 mm ± 1 mm	
	11. 195.0 mm ± 1 mm			
WEIGHT	447	Mistalation at all handless		
Weight:	147 g ± 7 g	Weight metal handle:	21 g ± 2 g	
Weight plastic handle:	8 g ± 0.8 g			
PERFORMANCE				
Stackability - dynamic:	Max: 30 kg top load on b			
Stacking tests	period of 2 months. Stac	kability depends on many factors a	gin raw material as stated below at 23°C over a nd the above data is meant as an indication only. ermine the viability of stacking and transportation.	
CLOSURE SYSTEM		HANDLE		
Lid type options:	Membrane, Standard, Tar	mper Standard handle	: Flexible plastic hanging	
	Evidence	Optional handle:	Metal	
Closure type:	Flex-off			
Tamper Evidence type:	Tamper Evidence lid			
DECORATION				
Decoration available: Dry Offset, IML				
Decoration area offset:	629 X 110/131 mm			
RAW MATERIAL (MEC	CHANICAL PROPERTIES)			
Raw material options:	PP			
Hot filling:	Up to 95° C	•		
Masterbatch colours: Colours according to Berry Superfos standard selected pantone colours.				
Hot temperatures: The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.				
Cold temperatures:	I temperatures: Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.			
QUALITY SPECIFICAT	TIONS			
Approvals:	amendments, relating to stated. In accordance wi	All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.		
Shelf life:	after the date of the deliv	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.		
Quality information:	considered acceptable ir	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.		
Compliance and product suitability: For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.				
www.superfos.com	Specifications a	are subject to change without notice.	Latest revision: 10-05-2019	