## Technical Datasheet

	UN SuperFlex Product no: Shape: Available lids:	9220 UN Round 2220 UN (S			
	VOLUME				
	Volume under lid:	4	21.6   ± 220 ml	Volume brimful:	22.1 l + 220 ml
	DIMENSIONS				
	External diameter to	p: 3	331 mm ± 3.5 mm	Height:	337 mm ± 3.5 mm
	External diameter bo		284.3 mm ± 3 mm	0	
	WEIGHT				
	Weight:	e	630 g ± 19 g	Weight metal handle:	58 g ± 3 g
	PERFORMANCE				
	Stackability - dynamic: Max: 50 kg top load on b			tainer at 23°	
	UN approval:		UN Group 2 and 3 solids with inside bag		
	Stacking tests		The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.		
	Special:		UN approval 1H2/Y21/S with inside bag 90 microns		
	CLOSURE SYSTEM			HANDLE	
	Lid type options:		Tamper Evidence, Standard	Standard handle:	Metal with roller grip
	Closure type:		Flex-off		
	Tamper Evidence type:		None		
	DECORATION				
	Decoration available	:	Dry Offset		
Decoration area offset: 9		et:	920 X 235 mm		
	RAW MATERIAL (MECHANICAL PROPERTIES)				
	Raw material options:		PP		
			Colours according to Berry Superfos standard selected pantone colours.		
	Hot temperatures:		The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.		
	Cold temperatures:		Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.		
	QUALITY SPECIFICATIONS				
Approvals:			All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.		
Shelf life:			The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.		
			Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.		
Compliance and product suitability:		duct suitability:	For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.		
	www.superfos.com		Specifications are subject	to change without notice.	Latest revision: 20-02-2024