## 

## Technical Datasheet

EasySnacking	g 89 x 89 mm 300 ml			
Product no:	8853			
Shape:	Square			
Available lids:	8857 (Membrane)	B100 8867 (Membrane)		
	B190 8868 (Membrane)	8858 (Membrane)		
	B000 8866 (Membrane)			
VOLUME				
Volume under lid:	300 ml			
DIMENSIONS				
Length top:	85.8 mm ± 0.5 mm	Width top:	85.8 mm ± 0.5 mm	
Length bottom:	67.6 mm ± 0.5 mm	Width bottom:	$67.6 \text{ mm} \pm 0.5 \text{ mm}$	
•		width bottom.	67.6 mm ± 0.5 mm	
Height:	64.7 mm ± 0.5 mm			
WEIGHT				
Weight:	8.8 g ± 0.9 g			
PERFORMANCE				
Stacking testsThe stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.				
CLOSURE SYSTEM	1			
Lid type options:	Membrane	Membrane		
Closure type:	Peel-off	Peel-off		
Tamper Evidence typ	be: None	None		
DECORATION				
Decoration available: IML				
RAW MATERIAL (M	ECHANICAL PROPERTIES)			
Raw material options: PP				
Masterbatch colours	: Colours according	Colours according to Berry Superfos standard selected pantone colours.		
Hot temperatures:	plastic packaging t relation to stacking	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.		
Cold temperatures:		Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.		
QUALITY SPECIFIC	ATIONS			
Approvals:	amendments, relat stated. In accordar	All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.		
Shelf life:	after the date of the	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.		
Quality information:	considered accept	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.		
Compliance and pro	duct suitability: For all information Compliance.	For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.		
www.superfos.com	Specificat	tions are subject to change without notice.	Latest revision: 31-01-2023	